

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 October 2003 (23.10.2003)


PCT

(10) International Publication Number  
WO 03/086767 A1

- (51) International Patent Classification<sup>7</sup>: B41J 2/05, B81B 7/04
  - (21) International Application Number: PCT/AU02/01164
  - (22) International Filing Date: 29 August 2002 (29.08.2002)
  - (25) Filing Language: English
  - (26) Publication Language: English
  - (30) Priority Data: 10/120,345 12 April 2002 (12.04.2002) US
  - (71) Applicant (for all designated States except US): SILVERBROOK RESEARCH PTY LTD [AU/AU]; 393 Darling Street, Balmain, New South Wales 2041 (AU).
  - (72) Inventor; and
  - (75) Inventor/Applicant (for US only): SILVERBROOK, KIA [AU/AU]; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
  - (74) Agent: SILVERBROOK, KIA; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
  - (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
  - (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: PUSHER ACTUATION IN A PRINTHEAD CHIP FOR AN INKJET PRINTHEAD



(57) **Abstract:** A plurality of nozzle arrangements (70) is positioned on the substrate (12) of printhead chip. Each arrangement includes a nozzle chamber structure (72, 74, 76, 78) positioned on the substrate and defines a nozzle chamber (80) from which ink is ejected. An ink-ejecting mechanism is operatively arranged with respect to the nozzle chamber structure. The ink-ejecting mechanism includes at least one moving component (106) displaceable to generate a pressure pulse within the nozzle chamber to eject ink. An actuator (92) is positioned on the substrate and has at least one working member (94) that is of a material having a coefficient of thermal expansion such that the working member is capable of substantially rectilinear expansion. An energy transmitting means interconnects the moving component and the working member so that energy generated by the working member as a result of expansion and subsequent contraction of the working member is transmitted to the moving component resulting in generation of said pressure pulse.



WO 03/086767 A1